

Granulators EM Series

Model 19/12 EM, 19/19 EM, 19/25 EM, 19/31 EM

CHARACTERISTICS

Compact and slow speed granulator especially designed for the recovery of small sprues. It can be fed by manipulator, robot or manually.



DESCRIPTION

- Minimum dust.
- Minimum energy consumption.
- Small dimensions
- Incorporated anti-friction lateral disks
- Long-lasting knives
- Sharpenable and adjustable rotor knives.
- Cassette type sharpenable rotor knives.
- Identical rotor knives throughout the whole range.
- Fast knife replacement.
- Maximum opening distance between bodies.
- Removable lower body.
- Quick access to screen.
- Minimum cleaning time.
- Standard model partially sound proof.
- Complies with CEE machinery standards.

OPTIONAL

- Sound-proof version.
- Great modularity, cyclones, bags, bins.
- Variable cutting speed.
- Special inlets for manipulators.

TECHNICAL DATA	19/12 EM	19/19 EM	19/25 EM	19/31 EM
Feed capacity (mm)	190/125	190/190	190/250	190/315
Ø cutting (mm)	165	165	165	165
Motor power (CV)	2-3	2-3	3-4	3-4-5,5
Motor power (kW)	1,5- 2,2	1,5- 2,2	2,2- 3	2,2- 3- 4
Cutting speed (r.p.m.)	200	200	200	200
Number of rotor knives	2 x 3	3 x 3	4 x 3	5 x 3
Number of adjustable knives	1 x 1	1 x 1	2 x 2	2 x 2
Ø screen hools (mm)	5	5	5	5
Output approximate according to material (kg/h)	30	45	60	75
Granulator approximate weight (kg)	215	240	260	280
Granulator measures (mm)	780x1300x475	780x1300x475	780x1300x500	780x1300x565